

Mandy

LINEAR LUMINAIRE WITH REPLACEABLE LIGHT SOURCE



valtavallo



Linear luminaire for office and kitchen workstations

Operating conditions

Usual sites for the Mandy include office and kitchen workstations where a slim luminaire is required. The luminaire can be installed on ceilings and walls. The socket and the switch available as accessories make the Mandy luminaire a versatile option. The default colour is white, but it is also available in grey and black.

Light source

The luminaire's replaceable light source is an EN 62776 standardised LED tube that can be replaced when necessary without a need to consider the manufacturer. We recommend Valtavallo G5 LED tubes as light sources. With the G5 Dimmable LED tube, the luminaire can be dimmed with a separate trailing edge dimmer. The luminaire can also be delivered with a dimmable LED tube and control unit suitable for SwitchDim or DALI solutions.

Maintenance

The luminaire itself is practically maintenance free, which means maintaining and renewing your lighting system is easy and fast – just change the light source.

Mandy

LINEAR LUMINAIRE WITH REPLACEABLE LIGHT SOURCE



valtavallo

Technical Specifications

Model	Mandy 60 cm	Mandy 120 cm	Mandy 150 cm
Dimensions, l x w x h, mm (*dimensions with SwitchDim or DALI control unit)	788 x 66 x 45 (*not available)	1398 x 66 x 45 (*1424 x 66 x 45)	1698 x 66 x 45 (*1724 x 66 x 45)
Weight, kg (*weight with SwitchDim or DALI control unit)	1,0 (*not available)	2,0 (* 2,1)	2,4 (*2,5)
Socket type	T8 / G13		
Input voltage	230 V AC, 50/60 Hz		
Protection	IP40		
Material	White powder coated steel, opal plastic cover		
Colour options	The default colour is white, available also in grey and black		
Warranty	5 years for the luminaire body; 5-7 years for the light source, depending on the model		
Connection	Through-wiring available by request: 5 x 1,5 mm ² or 5 x 2,5 mm ² , Feed-throughs at both ends (2 pcs.) and in the middle (2 pcs.) of the luminaire		
Installation	On the ceiling or wall surfaces with screws suitable for the material of the mounting surface		
Installation height	From workstation height to 3 m		
Recommended light source	G-series LED tubes		
Lighting control	Applicable to dimming with Trailing Edge, SwitchDim or Dali-control when Valtavallo G5 Dimmable LED tube is used as a light source.		
Accessories	Motion sensor (microwave sensor), SwitchDim, DALI, one- or two-piece socket, switch		
Additional information	Applicable for LED tubes only, can not be used with traditional fluorescent tubes. Valtavallo LED tubes to be ordered separately. LED tube is a standardized (EN 62776) light source that can be replaced regardless of the manufacturer.		