


Mirko

LINEAR LUMINAIRE WITH REPLACEABLE LIGHT SOURCE



valtavallo



Linear luminaire with replaceable light source for retail and office lighting solutions

Operating conditions

Mirko is a modern linear luminaire with a replaceable light source, which makes it suitable for a variety of uses. Thanks to its elegant design, the Mirko luminaire is particularly suitable for retail or office lighting solutions and for public spaces. By default, the luminaire is delivered with a glare reduction grid that preserves the light source's luminous efficacy. Also available with a dome with an opal finish. The default colour is white, but the luminaire is also available in grey and black.

Light source

The luminaire's replaceable light source is an EN 62776 standardised LED tube that can be replaced when necessary without a need to consider the manufacturer. We recommend Valtavallo G5 LED tubes as light sources. With the G5 Dimmable LED tube, the luminaire can be dimmed with a separate trailing edge dimmer. The luminaire can also be delivered with a dimmable LED tube and control unit suitable for SwitchDim or DALI solutions.

Installation and maintenance

Mirko can be mounted on a ceiling and wall surface, or suspended. The luminaire itself is practically maintenance free, which means maintaining and renewing your lighting system is easy and fast – just change the light source.

Mirko

LINEAR LUMINAIRE WITH REPLACEABLE LIGHT SOURCE



Technical Specifications

Model	Mirko 120cm	Mirko 150cm
Dimensions, l x w x h, mm (*dimensions with SwitchDim or DALI control unit)	1240 x 65 x 64 (*1540 x 65 x 64)	1540 x 65 x 64 (*1840 x 65 x 64)
Weight, kg (*weight with SwitchDim or DALI control unit)	2,5 (*3,2)	2,8 (*3,4)
Socket type	T8 / G13	
Input voltage	230 V AC, 50/60 Hz	
Protection	IP 20 (with an opal cover IP40)	
Housing material	Aluminium profile	
Cover material	By default, delivered with a glare reduction grid that preserves the light source's luminous efficacy. Also available with a dome with an opal finish.	
Colour options	The default colour is white, available also in grey and black.	
Installation	Ceiling or wall surface, lighting track, suspension cable.	
Installation height	2,5 - 5 m	
Connection	Through-wiring available by request: 5 x 1,5 mm ² or 5 x 2,5 mm ² , Feed-throughs at both ends (2 pcs.) of the luminaire, for suspension installation feed-throughs on the top of the luminaire	
Recommended light source	Lower spaces (2,5-3 m) G5 22 W LED tube Higher spaces (3-5 m) G5 35 W LED tube	
Lighting control	Applicable to dimming with Trailing Edge, SwitchDim or Dali-control when Valtavallo G5 Dimmable LED tube is used as a light source.	
Warranty	5 years for the luminaire, 5-7 years for the light source depending on the model	
Accessories	Motion sensor (microwave/PIR), SwitchDim, DALI, Stand-Alone DALI, pull cord switch, suspension wire kit	
Additional information	Applicable for LED tubes only, can not be used with traditional fluorescent tubes. Valtavallo LED tubes to be ordered separately. LED tube is a standardized (EN 62776) light source that can be replaced regardless of the manufacturer.	