

CERTIFICATE ENEC/FI 2018010



Our Ref. 288216-2

Product	Double-capped LED-lamp
Rating and principal characteristics	DRFD-8-25W-G13; 230 V AC, 50/60 Hz; ta: -20 °C - +40 °C; IP 20
Trade mark (if any)	Valtavalo
Type	E3 series
Name and address of the licensee and the manufacturer	Valtavalo Oy Veistämötie 8 FI-90620 OULU FINLAND
Is in conformity with	EN 62776:2015
As shown in the Test Report(s) No(s)	288216-2
It is authorized to use of the marks	ENEC 16 and FI

Validity This certificate is valid until 28 February 2023 provided that the Conditions for ENEC and FI certification are met. This certificate includes the right to use the ENEC 16 and FI mark under the condition that product changes (if any) will be approved at SGS Fimko before the product is brought onto market.

Directive information The certified product(s) fulfils requirements of above mentioned standard(s) which are harmonised under the Low Voltage Directive (2014/35/EU) at the date of issue of the certificate.

With the following limitations -

Date of issue 28 February 2018

SGS Fimko Ltd

Signature

Peter Fagerstedt

Certification Manager



This certificate has 2 pages



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Manufacturing site(s) Valtavalo Oy
 Tehdaskatu 15
 Korjaamo 4 C 59
 FI-87100 KAJAANI
 FINLAND

Is based on test / Our ref. 288216-2

Additional information

The E3 series includes following models:

Model	Wattage [W]	Length [cm]
VV08x045E3-yzz	8	45
VV10x060E3-yzz	10	60
VV15x090E3-yzz	15	90
VV20x120E3-yzz	20	120
VV25x150E3-yzz	25	150

x = F (opal cover)
 y= 8 (CRI 80) or 9 (CRI 90)
 zz = 30 (3000 K) or 40 (4000 K) or 50 (5000 K) or 65 (6500 K)